

# SUPPLIER | PROFILES

Special Advertising Section

## Viking Pump



Viking Pump offers the broadest range of sanitary rotary lobe pumps in the food industry today. If you need to transfer, meter or process any food or beverage products or ingredients, contact Viking Pump for application assistance.

With six major 3-A compliant pump series to choose from, the right Viking pump is available to handle nearly every food processing application. They include:

- SQ series aseptic process pumps, EHEDG certified for bacteria-tightness and steam sterilizability, with 8 sizes to 480 gpm.
- SteriLobe series pumps with bi-wing or 4-lobe rotor options, 15 sizes to 600 gpm. EHEDG certified for In-Place Cleanability.
- DuraLobe series bi-wing rotor pumps, 12 sizes to 600 gpm. EHEDG certified for In-Place Cleanability.
- Classic series tri-lobe rotor pumps, 11 sizes to 650 gpm.
- AccuLobe 5-lobe or tri-wing rotor pumps, to 7 gpm. EHEDG certified for In-Place Cleanability.
- RTP series truck-mounted tri-lobe rotor pumps, to 340 gpm.

Viking's Sanitary Products Group (which also offers Wright Pump circumferential piston pumps) provides application support and service through distributors specializing in food processing equipment. We understand the specialized needs of food and beverage processors, and are here to help.

Visit us at the Food Processing Machinery Expo in November.



### Contact:

Viking Pump Sanitary Group  
406 State Street  
Cedar Falls, IA 50613  
Phone: 319/266-1741  
Fax: 319/273-8157  
www.vikingpump.com  
www.wrightpump.com

## Waukesha Cherry-Burrell

### Waukesha Cherry-Burrell Products:

#### Universal I Series PD Pumps

Waukesha Cherry-Burrell's traditional "Can-Do Pump." Versatile in application, its reliability has made it the industry standard worldwide for more than 50 years.

- Easy cleaning and disassembly
- Flexible, three-way mounting
- Field interchangeable single and double "O" ring and mechanical seals
- Exclusive, non-galling Waukesha "88" alloy rotors
- 3-A and BISSC approved
- Maximum pressure: 200 psi (13.8 bar)
- Temperature range: -40° F. (-40° C.) to 300° F. (149° C.)

### Waukesha Cherry-Burrell Products:

#### Universal II Series PD Pumps

In addition to the proven operation and durability of the Universal Series, this pump includes advanced sanitation technologies, long life features and installation flexibility.

#### Features:

- Bi-directional flow
- Large diameter shafts for greater strength & stiffness
- Rotor/shaft connection sealed from the product zone
- Extended-life outer seal
- Mechanical seals standard
- 316 pump body standard; 316L pump body optional
- Heavy-duty bearing frame; stainless steel bearing frame optional
- Exclusive, non-galling Waukesha "88" alloy rotors for tighter running clearances and higher efficiencies
- Additional options: CIP capability, free draining body and cover for side mounted applications, seal flushing, steam-in-place, aseptic version
- Maximum pressure: 200-500 psi (13.8-34.5 bar), depending on model
- Temperature range: -40° F. (-40° C.) to 300° F. (149° C.)\*



An SPX Process Equipment Operation

### Contact:

SPX Process Equipment  
611 Sugar Creek Road  
Delavan, WI 53115  
Ph: 800.252.5200 or 262.728.1900  
Email: info@processequipment.spx.com  
Web: www.spxprocessequipment.com